

Start Your Intelligent & Instant Coffee Life

JL500 Series

Bean to cup coffee vending machine

Enjoy Your Bean Go Time

Jetinno Chief Expert Counselor JORIS HENDRIKS

Owner of 5 invention patents

Founder of Hendriks Coffee

High-end coffee machine designer

7 years in Spengler as product manager and corporate partner

15 years in Maas International as product designer and R&D manager



CONTENTS

- Product Highlights
- Product Features
- Core Components
- Product Parameters
- Product Size
- Optional Parts
- Customization Details
- Clean Products
- Product Certificates
- Our Services



Jetinno Hot Sale Product

Machine Software Update

We will always keep the machine's software timely updated, so that it will work smoothly and stable.

High Quality Components

The machine manufactured with high quality components, more reliable working and can effectively reduce malfunction possibility.

Fresh Beverages Extraction

JL500 makes freshly extracted beverages, including fresh coffee and fresh fruit juice and tea. Fresh extraction gives drinks the fresh and delicious flavors.







Fresh Coffee



ES Extraction



Tea drink



20+ drinks



Hot & Cold Drinks



Auto Milk Foam Frothing



Self Service



Touch Screen



Multiple Payments



Remote Access



Vending & Laborsaving



Automatic cleaning




High Quality Manufacturing With Craftsmanship



JETINO[®] Product features 07

High Quality Manufacturing With Craftsmanship






Make 20+ Hot & Cold Beverages

JL500 can produce more than 20 drinks, including hot and cold types of coffee, fruit juice and tea.

27-inch Touch Screen

Comes with a 27 inch touch screen, can also display ads for drinks promo. User friendly interface, easy to order drinks.




Remote Real-time Machine Monitoring

Can monitor the machine's status in real time via PC and a smart mobile, remote checking of drinks sales data and stock status. Also with machine malfunction alert push, convenient and laborsaving.

Auto Machine Cleaning

Comes with automatic machine cleaning function, cleaning time is programmable, ensure the machine's hygiene, easy machine maintenance and laborsaving.

Start Your Vendo Business With The Excellent JL500



Alert Light

Alert light will be on when drink production finished.



Manual Delivery Door

When drink production finished, the delivery door will unlock, safer to take away drinks.



Canister Nozzle Cover

Comes with a nozzle cover to keep the hygiene of powder storage.



Manual Water Discharge Switch

Designed with a manual water discharge switch, to completely discharge the water residue in the boiler.

Easy Use & Maintenance




Real-time Alert

When malfunctions happen, the console will push a notice.



Detachable Design

Machine's key components apply detachable design, convenient to detach and clean for deep cleaning, easy maintenance.



Auto Machine Self Cleaning

Designed with automatic cleaning function, the cleaning time is programmable, easy maintenance.



High Volume Waste bucket/Waste Water Bucket

Comes with high volume waste bucket and waste water bucket, has auto water full alert function.

Product Features 12

Jetinno SaaS Management

Support PC and mobile



Remote Control

Support remote control of recipes adjustment, machine setting, UI ads and video upload, machine system upgrade.

Malfunction Alert

Real time machine malfunction alert, can push notice to machine operator.

Comprehensive Data

Location deployment data, drink sale data, payment data, all these data statistics help operator better in machine operation and coffee vending business.

Product features

Powerful Machine Console Platform



- Drink Promo Tag Setting
- Drink Sale Report

JETIMO


- Ads Management
- Stock Management

Drink Data Bank

13

Modular Design

The modular design concept has been applied to coffee machine's R&D at the very beginning. Modular design brings more convenient machine maintenance, easier for deployment.




JETIMO[®]



Jetinno Patented Hydraulic System

- 2700W heating power, continuous and stable water temperature guaranteed
- Sweden Backerths 700ml stainless high-pressure boiler, max 25bar tolerance.
- USA EMERSON professional STB temperature control protective switch.
- Japan OMRON temperature/pressure sensor, real-time monitoring.
- Italy ULKA high -pressure electromagnetic pump, provides 9Bar extraction pressure.
- Other valve joints spare parts, flow meter are all Italy and German made.



Ditting EMH64 Grinder

- 64mm flat bur, made of stainless steel.
- Low grinding heat, no interference to coffee flavor.
- Multiple adjusting grades of grinding fineness.
- 125,000 times lifespan, long service life.




Professional coffee brewing system

• Removable brewer module design, easy for cleaning.

• 9bar 92°C Espresso extraction, compatible with low-pressure brewing.

• Jetinno PTC international patent, European time-honored brand applies the same type.

- Pre-infusion function to have saturated extraction.
- PTC heaters in brewing chambers, provide constant heating to solve low-temp of first cup.
- Built with 14g and 20g two brewing chambers, for different recipes.
- Detachable brewing chamber design, easy for deep-cleaning.
- Auto decompression function to discharge residual coffee liquid.



17



- Jetinno patent.
- Spraying and pre-infusion, better extraction.
- Adjustable brewing time, water temperature and water dose.
- Detachable components design, convenience of cleaning.
- Direct coffee powder dropping, no secondary pollution.
- Maximum 14g coffee or tea powder loading.
- Can be used both as coffee and tea brewer.





High speed stirring system

- Patented tech innovated by Jetinno.
- Detachable stirring chamber, easy for cleaning and maintenance.
- Up to 20000rpm stirring speed, rapid sufficient dissolution.
- Adjustable stirring speed for different recipes.(milk foam requires high speed, instant coffee and tea drinks require low speed).

JETINNO° Core Components



Canister

- Jetinno patent.
- Detachable design, convenience of cleaning.
- Powder screw design, precise control of powder.
- Food grade plastic, HSF security certified.



Automatic Cup Dispenser

- Jetinno patent
- Auto cup & cup empty detecting, monitoring of cup quantity and status.
- 5 cup columns design, automatic column switch.
- Suitable for multiple cup size, D70/73/80/90mm (paper cup).



Two-headed Pump

- Jetinno patent
- Real-time monitoring of water, water scarcity alert.
- Noise reduction design, working noise less than 60dB.
- Auto switch of water pumping from barrelled water.

Multi-function main board

- Designed and developed by Jetinno.
- 8 core Cortex A7 CPU, 2GHz.
- Multiple network ports for network connection.
- Multiple displaying format ports and dual screen displaying.
- Up to 10-way ports expansion.
- Android & Linux.

10 board

- Designed and developed by Jetinno.
- Quick response.
- Fast protection for malfunctioned unit.
- Precisely control all module units.
- Multiple ports expansion, can independently support 25-way control unit.
- Support various types of sensors, including temperature, humidity, flow and pressure.



Core Parts







Italy Fluid-o-tech Pump



Sweden Backerhts boiler



German AVS Römer joints



Italy ODE valve bank



USA EMERSON switch

Configurations	JL500-ESFB7C-PI	JL500-ES7C-PI	JL500-2FB8C-PI	JL500-IN8C-PI
Bean hopper	1	1	Х	X
Instant container	6	6	8	8
Ditting EMH64 Grinder	1	1	X	Χ
ES Brewer	1	1	X	Χ
Brewer(Tea)	1	X	2	Χ
Mixer	3	4	3	5
Boiler	1	1	1	1
Gear pump	1	1	X	X
Piston pump	Χ	Χ	1	1
Waste bin capacity	1	1	1	1
Waste water bucket	1	1	1	1
Drip tray full detector	\checkmark	\checkmark	\checkmark	\checkmark
Auto Cup Dispenser	\checkmark	\checkmark	\checkmark	\checkmark
Manual cup delivery door	\checkmark	\checkmark	\checkmark	\checkmark
Water supply		Default: direct water	Option: barreled water	
Internet Connection		Default: WIF	l; Option: 4G	
Payment	Ор	tion: WeChat/Alipay; Nay	yax, or other MDB protoc	ols
OS		Android, Lin	ux(Optional)	
BIB		Opti	onal	
Chiller		Opti	onal	
External Ice Maker		Opti	onal	
Auto cup lid capping module		Opti	onal	
SaaS platform		Opti	onal	
Top light box		Opti	onal	
Color customization		Opti	onal	

Mode	el La	you	t JL!	500-E	SFB7	7C-PI
C7	C6	C5	C4	С3	C2	C1
4L	4L	4L	4L	4L	4L	4L
Bean	Red tea	Cacao	Topping	Sugar	Creamer	Milo
*Materials in abov	FB Tei	Cup sy		Cooli	ng wat	

Daily Output: 250 Cups/Daily

*110V (Optional)

Configurations	Parameter specification
Operation interface	27"touch screen
Bean hopper	1x1.5kg
Instant canister	6 x 4.0L
Espresso Brewer	1x14g, 20g(Option)
Tea brewer	1x14g
Water boiler	1 x 700mL,2700W(220V)
Waste bin capacity	1x125 Cakes
Waste Water Bucket	1x15L, Drip tray full detector
Auto Cup Dispenser	D80mm cups, CustomD70/84/90mm
Drop-cup system	5 cup columns, 180 Cup (D80mm/10 Oz)
Cup cover dispenser	130
Power	220-240V 50/60Hz
Rated power	2700W (230V)
Dimension (W*H*D)	664*1830*720mm
Net weight	150kg

Main drinks: Espresso, American coffee (cold / hot), cappuccino, latte, mocha, milk, cocoa Fruit juice (cold / hot), milk tea, black tea

Drinks Outpt(based on protocol DIN18873-2 hourly output)

Espresso:124 cappuccino:105 American coffee:100 Café Crème:80

*110V (Optional)

Mode	Model Layout JL500-ES7C-PI						Configurations	Parameter specification			
							Operation interface	27"touch screen, 27"screen+10.1" touch screen			
C7 4L	C6 4L	C5 4L	C4 4L	C3 4L	C2 4L	C1 4L	Bean hopper	1x1.5kg			
	æ		g		e		Instant canister	6 x 4.0L			
_	t tea	0	i.	_	E		Espresso Brewer	1x14g, 20g(Option)			
ear	nstant	aca	Торр	ga	eal	Milo	Chiller	Optional, water output speed 17ml/s			
Be	lus	Ca	T	Suga	Suga Crea		Boiler	1 x 700mL,2700W(220V)			
							Waste bin capacity	1x125 Cakes			
							Waste Water Bucket	1x15L, Drip tray full detector			
EMH64	Mixer Mixer Mixer		Mixer		Auto Cup Dispenser	D80mm cups, Custom D70/84/90mm					
										Drop-cup system	5 cup columns, 180 Cup (D80mm/10 Oz)
						<u>4</u> -	Cup cover dispenser	130			
							Power	220-240V 50/60Hz			
	Cup system						Rated power	2700W (230V)			
							Dimension (W*H*D)	664*1830*720mm			
							Net weight	150kg			
Cooling water unit					ng wat	er un <u>it</u>	Main drinks:Espresso, Americar	n coffee (cold / hot), cappuccino, latte, mocha, milk, cocoa Fruit juice (cold / hot)			
*Materials in ab	ove canisters	are only for	reference					Truit juice (cota / flot)			

Drinks Outpt(based on protocol DIN18873-2 hourly output)

Daily Output: 250 Cups/Daily

Espresso:124

cappuccino:105

American coffee:100

*110V (Optional)

Model Layout JL500-2FB8	OC_DI	Configurations	Parameter specification
		Operation interface	27"touch screen, 27"screen+10.1" touch screen
C8 C7 C6 C5 C4 C3 C 4L 4L 4L 4L 4L 4L 4		Tea canister	2x 4.0L
a 2	7	Instant canister	6 x 4.0L
Tea Tea Int		Filter brewer	2x14g
Fresh Te Fresh Te Instant Instant	ınsta	Chiller	Option, Water output speed 17ml/s
Fresh Fresh Install In		Boiler	1 x 700mL,2700W(220V)
		Waste bin capacity	1x125 Cakes
	1/	Waste Water Bucket	1x15L, Drip tray full detector
Mixer Mixer	Mixer	Auto Cup Dispenser	D80mm cups, Custom D70/84/90mm
FB Tea Brewer		Drop-cup system	5 cup columns, 180 Cup (D80mm/10 Oz)
		Cup cover dispenser	130
		Power	220-240V 50/60Hz
		Rated power	2700W (230V)
Cup system		Dimension (W*H*D)	664*1830*720mm
		Net weight	150kg
Cooling w	ater unit	Main drin	ks:Tea drinks + Instant drinks
*Materials in above canisters are only for reference			

Drinks Outpt(based on protocol DIN18873-2 hourly output)

Daily Output: 250 Cups/Daily

American coffee:100 cappuccino:105




*110V (Optional)

Model Layout JL500-IN8C-PI		Configurations	Parameter specification							
C8			Operation interface	27"touch screen, 27"screen+10.1" touch screen						
4L	C7 4L	C6 4L	C5 4L	C4 4L	C3 4L	C2 C1 4L 4L		Instant canister	8 x 4.0L	
		æ	fee		<u></u>	5		Mixer	5	
ix2	<u>×</u>	t	Cof	9	E E	ing		External Ice Maker	Optional, 1.5kg/bucket	
Pre-mix2	Pre-mix1	Instant tea	Instant Coffee	Ca	Creame	pp	2	Chiller	Option, Water output speed 17ml/s	
Pre	Pre	lns	Inst	Ca	2	Toppi	5	Boiler	1 x 700mL,2700W(220V)	
								Bottled water	3x18.9L	
					Mixer Mixer			Waste Water Bucket	1x15L, Drip tray full detector	
Mixe	er (Mixer	Mixer	N				Auto Cup Dispenser	D80mm cups, Custom D70/84/90mm	
	Z 7			\sum_{i}						
7	y - ¬	~ ~~ _				Cup cover dispenser	130			
				Power	220-240V 50/60Hz					
								Rated power	2700W (230V)	
	Cup system		Dimension (W*H*D)	664*1830*720mm						
		Net weight	150kg							
*Materials i	Cooling water unit		Mai	n drinks: Instant drinks						

Daily Output: 250 Cups/Daily





Package size :820 (W) *780 (D) *1900 (H) mm



Optional module	Optional or not
BIB peristaltic pump	Optional
Chiller	Optional
External Ice Maker	Optional
Auto cup lid capping module	Optional
Human Induction	Optional
UV light	Optional
Electric meter	Optional
4G	Optional

Payment module	Optional or not
Facial scan payment	Optional
Reverse QR Code payment	Optional
Paper currency validator	Optional
Coin validator	Optional
RFID payment	Optional
MDB Cashless	Optional

Optional Parts 30



JETIMO°

BIB module

Function: connect to concentrates to make BIB drinks.

Item	Parameter
Module dimensions (W*H*D)	156x350x280mm
BIB bag weight	3kg
Port size	Dual head M30
Flow	$600\pm10\%$ ml/min(suction head 1 meter, pump head 0.5 meter)
Working environment	Temperature: 0~60°C Relative humidity <85%RH
Matched tube	24#
Power	32W

31



Jetinno Patented Water Cooler

- Guarantee of continuous output of cool water
- 0~6.5°C water temperature, 17mL/s cool water output speed
- Apple R134a/R600a coolant
- German instant cooling technology






Ice Maker

Jetinno Patented ice making unit

Items	Parameters
Working Environment	5-35°C, 90%H humidity
Coolant	R290
Water Storage	1.5kg/bucket
Ice Type	Ice cube 1.2g/each
Ice Output	13 cups 180g/cup
Daily Output	72kg/day
First Output	<25min
Ice Full Time	90min



UI customization

Name	Position	Width	Height	Format
Light box	А	664mm	<300mm	Al or cdr
Brand LOGO	В	<600mm	<700mm	Al or cdr
UI LOGO	С	327PX	66PX	PNG
UI drink picture	D	287PX	287PX	PNG
Video ads	E	1920PX	1080PX	MP4

33

Deep customization

Name	Item
	Open underlying control serial port protocol, support customer self-developed APP.
Ports	Open network interface(TCP/IP), support customer self-developed server.
	Open RESTful interface, support customer online store and data system.
OS	APP application layer customizable development (Linux, Android).



Product: Coffee machine tea brewer cleaner

Use: used for coffee machine tea brewer cleaning

Ratio: 2 pills with 5.67L water

Details: 4g/pill, 120 pills/bottle, 12 bottles/case



Product: coffee machine boiler cleaner

Use: used for coffee machine boiler cleaning

Ratio: 200g powder with 3.9L water

Details: 1kg/bottle, 6 bottles/case



Product: coffee machine cleaner

Use: used for coffee machine brewer cleaning

Details: 2g/pill, 100 pills/can, 12 cans/case



Product: cleaning brush

Use: used for coffee machine cleaning

and maintenance

Details: general use



Product: tower

Use: used for coffee machine cleaning

and maintenance

Details: general use



Security Certification

CB

 ϵ



Food Contact Material

EU 1935/2004 European food test


Europe

LFGB German






Europe EVA energy consumption level A







Guangzhou Jetinno Intelligent Equipment Co., Ltd

Address: 4F, No. 2, Ruitai Road, Huangpu District, Guangzhou, China

Tel:400-017-9997

E-mail: inquiry@jetinno.com

Website:www.jetinno.com www.jetinnovending.com